

NOTES:
CLEANOUT SHALL BE PROVIDED AT OR NO MORE THAN FOUR (4) FEET ABOVE, THE BASE OF EACH VERTICAL WASTE OR SOIL STACK.

VENDING ROOM FLOOR DRAINS SHALL BE ACCESSIBLE AND READILY CLEANED, AND SHALL BE LOCATED SO THAT THEY ARE EASILY VISIBLE.

ALL EMPLOYEE OR PUBLIC SINKS SHALL BE A MAXIMUM OF SIX AND A HALF (6 1/2) DEEP AND MOUNTED WITH THE TOP EDGE A MAXIMUM OF THIRTY-FOUR (34) INCHES ABOVE THE FLOOR. -THE SINK DEPTH FOR LAVATORY SINKS DOES NOT APPLY.

ICE MACHINE, COFFEE, TEA, JUICES, OR SIMILAR BEVERAGE DISPENSERS SUPPLIED WITH POTABLE WATER SHALL BE PROVIDED WITH AN APPROVED BACKFLOW PREVENTER DEVICE APPROPRIATE FOR EACH TYPE OF MACHINE.

EMERGENCY EYE WASH FIXTURE SHALL HAVE THE PROPER MIXING VALVE ASSE 1071-1 LISTED AND SHALL MEET THE REQUIREMENTS OF THE ANSI/ISA 7339.1-2004 INSTALLED TO DELIVER TEPID DEVICES. WATER TEMPERATURE.

ALL HAND-HELD SHOWER SPRAY UNIT(S) SHALL HAVE AN ATMOSPHERIC VACUUM BREAKER COMPLYING WITH ASSE 1041 INSTALLED IN-LINE ON THE HOSE.

AIR CHAMBER(S) SHALL BE INSTALLED IN THE RISER WATER PIPES AND SHALL BE 8" EAST THIRTY-FOUR (34) INCHES IN LENGTH AND AT LEAST THE SAME SIZE AS THE RISER.

ALL WATER CLOSETS TO BE LOCATED EIGHTEEN (18) INCHES CENTER FROM THE SIDEWALL WITH APPROPRIATE SIZE GRAB BAR INSTALLED.

ALL FLOOR DRAINS IN THE IMMEDIATE FOOD PREP AREA SHALL DISCHARGE INTO THE GREASE INTERCEPTOR.

WASHING MACHINES SHALL HAVE THE APPROVED INTERCEPTOR OR SIMILAR DEVICE TO PREVENT MATERIALS DETRIMENTAL ENTERING INTO THE SEWAGE SYSTEM.

ELEVATOR SUMP PUMP SHALL INDIRECTLY CONNECT TO THE SANITARY DRAIN.

BACKFLOW DEVICES SHALL BE TESTED AND APPROVED BY A CROSS CONNECTION CONTROL DEVICE INSPECTOR (CCCDI) BEFORE INITIAL OPERATION.

PLUMBING FIXTURES SHALL DELIVER HOT WATER AT A MINIMUM OF 120° FAHRENHEIT, EXCEPT FIXTURES REQUIRED TO DELIVER A MAXIMUM OF 110° FAHRENHEIT.

HOT AND COLD WATER SUPPLY PIPES FEEDING THE WASHING MACHINES SHALL HAVE THE APPROVED BACKFLOW PROTECTION.

A DRAIN DOWN VALVE SHALL BE INSTALLED ON THE DISCHARGE SIDE OF THE METER VALVE.


ALL ACCESSIBLE LAVATORY SINK AND SHOWERS SHALL BE INSPECTED BY PLUMBING INSPECTOR TO CONFIRM DELIVER TEMPERED WATER NOT TO EXCEED 110° FAHRENHEIT.

A PLUMBING INSPECTOR SHALL FIELD VERIFY THE DRAIN, WASTE, VENT AND WATER DISTRIBUTION SYSTEM SHALL BE PROPERLY SIZED IN ACCORDANCE WITH THE APPROPRIATE TABLES FOUND IN 840, APPENDIX A.

— SANITARY LINE
- - - HOT WATER
- - - COLD WATER

GAS WATER HEATER SCHEDULE					
MAKE & MODEL NO.	QUAN.	TANK CAP. GAL.	BTUH INPUT	RECOVERY GPH @ 100°F	REMARKS
CYCLONE XE	2	100 EA.	199,990 EA.	229 EA.	
-	-	-	-	-	-

PLUMBING FIXTURE SCHEDULE			
DESIGNATION	MANUFACTURER	PART#	DESCRIPTION
WC-1	KOHLER	K-3609	WHITE OVAL UNDERCOUNTER LAVATORY WITH AMERICAN STANDARD 2084.101 LEVER HANDLE LAV FAUCET; McCGURE 15SLAT LEVER ACTIVATED DRAIN STOPPER; NO. R-19-C BRASS CRAFT
WC-2	KOHLER	K-3575	WHITE OVAL UNDERCOUNTER LAVATORY WITH AMERICAN STANDARD 2084.101 LEVER HANDLE LAV FAUCET; McCGURE 15SLAT LEVER ACTIVATED DRAIN STOPPER; NO. R-19-C BRASS CRAFT
LAV-1 HDGP	KOHLER CAXTRON	K-2210-N	WHITE OVAL UNDERCOUNTER LAVATORY WITH AMERICAN STANDARD 2084.101 LEVER HANDLE LAV FAUCET; McCGURE 15SLAT LEVER ACTIVATED DRAIN STOPPER; NO. R-19-C BRASS CRAFT
LAV-2	KOHLER CAXTRON	K-2210-N	WHITE OVAL UNDERCOUNTER LAVATORY WITH AMERICAN STANDARD 2084.101 LEVER HANDLE LAV FAUCET; McCGURE 15SLAT LEVER ACTIVATED DRAIN STOPPER; NO. R-19-C BRASS CRAFT
SH-1 HDGP	KOHLER	VIKRELL SHOWER PAN	34" x 60" HIGH GLOSS VIKRELL WHITE SINGLE PC. SHOWER PAN WITH DRAIN IN CENTER OF PAN. SURROUNDS: MINCEY MARBLE MANUFACTURING INC. #75-DS PANELS MUST EXTEND FINISH TO BE AURORA OR LINEN, MATTE FINISH W/ "OLD WORLD STYLE" OR DIAMOND DESIGN SURROUND. 1/2" SURFACE MOUNT SOAP DISHES (INCLUDING CORNER MOUNT) & 2" TRIM PIECES (OPT.) MUST BE USED. SEE BUILDING & FINISHING SPECIFICATIONS FOR MORE DETAILS OF SURROUNDS. NOTE: SHOWER/TUB CONTROL VALVE MUST BE OPPOSITE THE SHOWER HEAD. THE SHOWER HEAD MUST REMAIN ON THE SAME WALL AS THE TOILET EXCEPT IN THE 14' WIDE KING ROOM WHERE THE TOILET IS NOT ADJACENT TO THE TUB/SHOWER. NOTE: NON SHRINKING MORTAR TO BE USED FOR BEDDING BASE.
S-1	KOHLER	K6579-2-96	18 90° TYPE 302 STAINLESS STEEL SINGLE BOWL UNDERMOUNT SINK WITH KOHLER NO. K15840-K-CP BAR SINK FAUCET; KOHLER NO. K15850-4R POLC HANDLE KIT; SUMP-N-LOC NO. 33306 STRAINER; BRASS CRAFT NO. R-19-C CP ANGLE STOP; BRASS CRAFT NO. 649 ESCUTCHEON; BRASS CRAFT NO. 1-20A
S-2	ELKAY	LR3122	18 90° TYPE 302 STAINLESS STEEL SINGLE BOWL SELF RIMMING SINK; 31"x22" OVERALL DIMENSIONS: 26"x16"x7 LK-2443 GOOSE NECK FAUCET & SPRAY, & VALVED ANGLE VALVES.
LT-1	MUSTEE	26F	DOUBLE FLOOR-MOUNTED LAUNDRY TRAY, MOLDED DURASTONE WITH LEGS; WITH KOHLER NO. K-11935-U LAUNDRY TRAY FAUCET; PROVIDE WOODFORD MODEL 24
MSB-1	MUSTEE	63M	DURASTONE FLOOR-MOUNTED 24x24x10 SERVICE SINK WITH CAMBRIDGE NO. 2819 RCP SERVICE SINK FAUCET; MUSTEE NO. 65.700 HOSE & HOSE HOLDER; MUSTEE NO. 65.600 MOP HANGER; MUSTEE NO. 63.401 BUMPER GUARDS; MUSTEE NO. 67.2424 WALL GUARDS & MUSTEE NO. 65.308 DRAIN SEAL
WB-1	GUY GREY	BED200	WASH MACHINE BOX WITH TWO(2) 1/2" MIP/ SWEAT VALVE - 2" TREADED DRAIN - 20 DUPLEX RECEPTACLE AND 30 AMP THREE WIRE 220V RECEPTACLE
WH-1	CYCLONE XE	BTH-199	155000 BTU/HR. INPUT EXTRA HIGH EFFICIENCY; TANK TYPE 100GPI.
HB-1	JOSAM	71050	CAST BRONZE NON-FREEZE WALL HYDRANT W/STAIN BRASS NIKALOY FACE 3/4" N.P.T. OUTLET, INTEGRAL VACUUM BREAKER-BACKFLOW PREVENTER, PRESSURE RECEIVER VALVE; CONTROL KEY OPERATED.
TMV	BRADLEY	559-3400	



GENERAL NOTES

ALL PLUMBING AND ELECTRICAL WORK SHALL BE IN ACCORDANCE WITH THE LATEST EDITIONS OF THE NATIONAL PLUMBING CODE, THE NATIONAL ELECTRICAL CODE, AND THE INTERNATIONAL MECHANICAL CODE. ALL WORK SHALL BE SUBJECT TO THE APPROVAL OF THE LOCAL BUILDING DEPARTMENT. ALL MATERIALS SHALL BE NEW AND OF THE BEST QUALITY AVAILABLE. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE LATEST EDITIONS OF THE NATIONAL PLUMBING CODE, THE NATIONAL ELECTRICAL CODE, AND THE INTERNATIONAL MECHANICAL CODE. ALL WORK SHALL BE SUBJECT TO THE APPROVAL OF THE LOCAL BUILDING DEPARTMENT. ALL MATERIALS SHALL BE NEW AND OF THE BEST QUALITY AVAILABLE.

MAUSET ARCHITECTURAL SERVICES
* Architects
* Planners
* Consultants
* Construction Management
* Rule 5 and MSA Filing
PHONE (574) 557-8500
FAX (574) 557-0808
112 NORTH MAIN STREET
GOSHEN, INDIANA 46526

SSC CONSTRUCTION
Serving Indiana, Illinois, Wisconsin, Michigan, Ohio and Arizona

MERRILLVILLE SCHOOL

6705 MERRILLVILLE RD.
MERRILLVILLE, IN 46410

REVISIONS:	

DATE: _____
JOB NO.: MAS-17-136
NAME: PLUMBING PLAN

SHEET: **P101**